

## Drain body The Universal DN 100, 3 inlets, w. backwater valve



### Article information

Item no.: 27600  
GTIN: 4026092085141  
Price group: 10

### Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

### Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PP

#### Variant

Waterproof flange:  
Waterproofing layer on the drain body:  
Sealing water height:  
Mechanical backwater flaps:

Pre-assembled at the factory  
Connection flange  
60 mm  
2

#### General characteristics

Colour:  
Standard:  
Nominal size (DN):  
Outer diameter (OD):  
Type of wastewater:  
Installation situation:  
Delivery state:  
Backwater protection:

black  
EN 1253  
100  
110 mm  
without sewage  
floor slab installation  
installation-ready  
Type 5

#### Dimensions

Net weight:  
Gross weight:  
Vertical adjustment:  
Length:  
Width:  
Height:

2,31 kg  
2,31 kg  
vertically adjustable upper section  
380 mm  
285 mm  
190 mm

|                         |          |
|-------------------------|----------|
| Packaging dimension:    | length   |
| Packaging dimension:    | width    |
| Packaging dimension:    | height   |
| Tank/drain body         |          |
| Material of drain body: | PP       |
| System:                 | lateral  |
| Coverage features       |          |
| Odour trap:             | included |