


The Ultraflat 79 floor drain DN 50, Des grating





Article information

Item no.: 44700.62 GTIN: 4026092080924

Price group: 10

Advantages

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant

System: 125
SonicControl: optional
Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1
Nominal size (DN): 50
Outer diameter (OD): 50 mm
purchasable by service partner: No

Dimensions

Vertical adjustment:88 - 139 mmNet weight:0,85 kgGross weight:1,01 kg

Vertical adjustment: vertically adjustable upper section

Length: 227 mm
Width: 163 mm
Height: 79 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Tank/drain body

Number of outlets: 1
Material of drain body: ABS
System: lateral

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 120 mm
Height of cover: 16 mm
Length of cover: 120 mm
Surface: ground

Frame material: Stainless steel 14301

Cover locking: unlocked

Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length:132 mmRim material:132 mmShape of upper section:squareUpper section material:ABSOdour trap:included