


The Ultraflat 54 floor drain DN 50, WaD, Des grating





Article information

Item no.: 44750.62M GTIN: 4026092080856

Price group: 10

Advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant

System: 125 SonicControl: optional

Waterproofing layer on the drain body: Factory-fitted sealing collar (WaD) according to DIN

18534

Water supply: W3-I Sealing water height: 22 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
purchasable by service partner: No

Dimensions

Vertical adjustment: 63 - 116 mm
Net weight: 0,9 kg
Gross weight: 1,04 kg

Vertical adjustment: vertically adjustable upper section

Length: 246 mm Width: 200 mm Height: 54 mm



Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 120 mm
Height of cover: 16 mm
Length of cover: 120 mm
Surface: ground

Frame material: Stainless steel 14301

Cover locking: unlocked

Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length:132 mmRim material:132 mmShape of upper section:squareUpper section material:ABSOdour trap:included