

Practicus drain body DN 50, Vertical outlet



Article information

Item no.: 45250
GTIN: 4026092033579
Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

| | |
|---|-------------------|
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics

| | |
|--------------------------|---------------------------|
| Standard: | EN 1253-1 |
| Nominal size (DN): | 50 |
| Outer diameter (OD): | 50 mm |
| Inlet max. scoring (DN): | Z-19.53-2414,Z-19.17-1719 |

Dimensions

| | |
|----------------------|---------|
| Net weight: | 0,59 kg |
| Gross weight: | 0,7 kg |
| Diameter: | 135 mm |
| Height: | 191 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|----|
| Number of outlets: | 1 |
| Material of drain body: | PP |

System: vertical

Coverage features

Odour trap: included