

## Shower channel Linearis Compact L: 650 mm, DN50, enclWPM, 304 STcov, K3



## **Article information**

Item no.: 45600.62 GTIN: 4026092048184

Price group: 10

## **Advantages**

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

## **Description**

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant

System: 125 SonicControl: prepared

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water supply: W2-I
Sealing water height: 22 mm
Discharge rate (l/s) with 10 mm backwater: 0,6
Discharge rate (l/s) with 20 mm backwater: 0,7
Discharge rate (l/s) without backwater: 0,5 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
purchasable by service partner: No

**Dimensions** 

Net weight: 1,85 kg Gross weight: 2,22 kg Outer dimension, length: 715 mm 80 - 140 mm Installation depth: Width: 191 mm Heiaht: 80 mm Packaging dimension: length Packaging dimension: width



Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Cover locking: placed

Load class: K 3 (EN 1253-1)
Grating colour: optionally tileable

Rim length: 66 mm
Rim material: 650 mm
Max. flooring height: 15 mm
Upper section material: ABS
Odour trap: included