

Upper section, Linearis Compact L: 1150 mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47812S

GTIN: 4026092079942

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Variant

System: 100 SonicControl: yes

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water supply: W3-I
Sealing water height: 50 mm
Discharge rate (l/s) with 10 mm backwater: 0,6
Discharge rate (l/s) without backwater: 0,5 mm

General characteristics

Nominal size (DN): 100
Outer diameter (OD): 100 mm
purchasable by service partner: No

Dimensions

Net weight: 2,62 kg Gross weight: 3,9 kg Outer dimension, length: 1215 mm Installation depth: 80 - 140 mm Width: 136 mm Height: 77 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height



Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Cover locking: placed

Load class: K 3 (EN 1253-1)
Grating colour: optionally tileable

Rim length: 66 mm
Rim material: 1150 mm
Upper section material: ABS
Odour trap: included