

## Yard drain System 100, vert., slot grat., B 125



## **Article information**

Item no.: 67110B GTIN: 4026092039373 Price group: 10

## **Advantages**

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

## Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant System: Contents of sludge trap:	100 yes
General characteristics Nominal size (DN):	100
Dimensions Net weight: Gross weight: Packaging dimension: Packaging dimension: Packaging dimension:	2,9 kg 2,9 kg length width height
Tank/drain body Number of outlets: Material of drain body: System:	1 Polymer vertical
Coverage features Type of cover: Cover material: Colour of cover: Width of cover:	Round slotted cover Ecoguss black 247 mm



Length of cover: Surface: Cover locking: Load class: Shape of upper section: Upper section material: Contents of sludge trap: Odour trap: 247 mm EDM Lock & Lift B 125 (EN 124) square Ecoguss yes no