


Chamber module LW 1000 floor slab Access LW 600, 2880-3129 mm, Class A/B





Article information

Item no.: 8740060 GTIN: 4026092065754 Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

. .

~

. . ..

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

General characteristics	
Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	underground installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Inlet max. scoring (DN):	Z-42.1-527
Dimensions	
Net weight:	194 kg
Gross weight:	227 kg
Groundwater resistant from lower edge of base section:	3000 mm



Installation depth: Vertical adjustment: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of inlets: Clear width of tank (LW): Clear width of entry (LW):

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Height of cover: Length of cover: Surface: Cover locking: Load class: Tightness: 2880 - 3129 mm vertically adjustable upper section 1200 mm length width height

150 mm 1000 mm 600 mm

Round cover plate Grey iron black 648 mm 95 mm 648 mm Grey iron unlocked B 125 (EN 124) surface water resistant